

Sump Gas 6216T-8116T Cartridges

Separation : Gas / Liquid
Equipment : FILTER
Media : disposable
Technical

Reference

6216 T and 8116 T (coalescent cartridges).
The two cartridges differ only by their length.

Application

Elimination of the oil mists at exit of
the blowhole of heat engines.

Technical data

Functional

Filtration rating: 5 μ at 90%
(new cartridg
Temperature < 150 °C

Geometrical

External diameter : 160 +6/-0 en mm
Internal diameter : 92 +/- 2 en mm
Height : 625 (6216) -0/+6 en mm
818 (8116) -0/+6 en mm

Maintenance

The cartridge must be regularly changed.
DP new: 8mmCE, DP clogging 40mmCE

Life span

Change the cartridge @ DP= 40mmCE

Flow rate (gas)

@ 8mmCE, 425 l/mn (6216), 710 l/mn (8116).

Protection of employees:

Avoid the contact with the cartridges saturated
with oil products.
Allergic reactions or others can be noted.

Destruction:

Accordingly to the French environmental code, article R 541-8, annex Two the **LEFCO**[®] oil car-
tridges are part of the categories 15.02.02.

A special plastic bag is provided to wrap up the used cartridge. These cartridges must be sending
towards an authorized treatment center. A list of these centers could be indicated on demand.